



ACOUSTICGYPS PN 50X40 GUIDING PARTITION PROFILE

TU 25.11.23-001-21056832-2019

TNVED 7308909809

DESCRIPTION

The reinforced profile for frame sheathed structures with the use of GKLZ (Soundproofing Gypsum Board), GSP (Gypsum Chipboard), GVL (Gypsum-Fibre Board) is made by steel band cold-rolling method. Serves as guiding elements for studs PC 50x50. Recommended for use in GKLZ AcousticGyps systems.

COMPOSITION

– galvanized steel.

MODIFICATIONS

Modifications	Length, mm	Width, mm	Thickness, mm	Height, mm	Weight, kg
AcousticGyps PN 50x40	3 000	50	0,6	40	1,72

APPLICATION

- for frames of sound absorbing partitions and wall coverings;
- for installation of connection element between studs.

FEATURES

- AcousticGyps profile is made of high grade steel of 0.6 mm thickness which ensures stiffness of structure and allows to sheath it using heavy multilayer materials and increases holding strength of fasteners in the profile;
- all profiles are marked with "AcousticGyps" thus preventing falsification;
- special strengthening ribs impart strength to the structure;
- every profile meets quality control standards.

PACKAGING AND TRANSPORTATION

Modifications	Package	No. of Profiles per Briquette, pcs	No. of Briquettes per Pallet, pcs	No. of Profiles per Briquette, linear m.	No. of Profiles per Palette, linear m.	Pallet Size, HxWxL, mm	Pallet Weight, kg
AcousticGyps PN 50x40	briquette	12	36	36	1 296	550x930x3000	760

Loading into trucks is performed by pieces, briquettes, and pallets according to Order.